

フリーストップヒンジのトルク一覧表

Torque List for Free Stopping Hinge

■トルク一覧 Torque List

※設定トルク値は常温環境 (25°C±5°C) の値になります。 Initial torque value : 25°C±5°C at room temperature.
 ※◆は基準トルク値になります。 ◆ is basic torque value.

型番 Model No.	設定トルク値 Initial torque value N・m (kgf・cm)						形状 Forms	頁 Page
	0.05 (0.5)	0.1 (1)	0.5 (5)	1 (10)	5 (50)	10 (100)		
TH-125-H				4.90 ^{±0.98} (50 ^{±10})	◆		平型タイプ Flat-type	2-103
TH-125-1				◆ 1.96 ^{±0.39} (20 ^{±5})				2-103
TH-125-2				◆ 1.37 ^{±0.39} (14 ^{±4})				2-103
TH-125-3				◆ 1.08 ^{±0.39} (11 ^{±4})				2-103
TH-125-4				◆ 0.69 ^{±0.20} (7 ^{±2})				2-103
TH-125-5		◆ 0.34 ^{±0.10} (3.5 ^{±1})						2-103
TH-146				0.25~1.96(2.5~20)				2-113
TH-149-1				◆ 1.57 ^{±0.39} (16 ^{±5})				2-104
TH-149-2				◆ 0.59 ^{±0.25} (6 ^{±2.5})				2-104
TH-149-3		◆ 0.2 ^{±0.15} (2 ^{±1.5})						2-104
TH-151				◆ 2.94 ^{±0.49} (30 ^{±5})				2-111
TH-164				◆ 2.94 ^{±0.2} (30 ^{±2})				2-123
TH-165-1				◆ 1.57 ^{±0.39} (16 ^{±4})				2-105
TH-165-2				◆ 0.59 ^{±0.25} (6 ^{±2.5})				2-105
TH-165-3		◆ 0.2 ^{±0.15} (2 ^{±1.5})						2-105
TH-166				◆ 0.8 ^{±0.3} (8.1 ^{±3.1})				2-109
TH-170-1				◆ 2.94 ^{±0.44} (30 ^{±4.5})				2-115
TH-170-2				◆ 1.47 ^{±0.29} (15 ^{±3})				2-115
TH-172-1				◆ 1.57 ^{±0.39} (16 ^{±4})				2-106
TH-172-2				◆ 0.59 ^{±0.25} (6 ^{±2.5})			2-106	
TH-172-3		◆ 0.2 ^{±0.15} (2 ^{±1.5})					2-106	
TH-173-1		◆ 0.14 ^{±0.05} (1.4 ^{±0.5})					2-114	
TH-173-2		◆ 0.08 ^{±0.02} (0.8 ^{±0.2})					2-114	
TH-175				◆ 0.45 ^{±0.2} (4.6 ^{±2})			2-107	
TH-157				◆ 0.735 ^{±0.147} (7.5 ^{±1.5})			隠しタイプ Hidden-type 2-112	
TH-122-1A				◆ 1.37 ^{±0.2} (14 ^{±2})			2-117	
TH-122-2A				◆ 1.08 ^{±0.15} (11 ^{±1.5})			2-117	
TH-122-3A				◆ 0.69 ^{±0.1} (7 ^{±1})			2-117	
TH-122-4A		◆ 0.34 ^{±0.05} (3.5 ^{±0.5})					2-117	
TH-134-1A				◆ 1.37 ^{±0.2} (14 ^{±2})			2-118	
TH-134-2A				◆ 1.08 ^{±0.15} (11 ^{±1.5})			2-118	
TH-134-3A				◆ 0.69 ^{±0.1} (7 ^{±1})			2-118	
TH-134-4A		◆ 0.34 ^{±0.05} (3.5 ^{±0.5})					2-118	
TH-139-1				◆ 0.69 ^{±0.15} (7 ^{±1.5})			2-125	
TH-139-2		◆ 0.29 ^{±0.07} (3 ^{±0.7})					ブラケットタイプ Bracket-type 2-125	
TH-139-3		◆ 0.15 ^{±0.05} (1.5 ^{±0.5})					2-125	
TH-143-1				◆ 3.92 ^{±0.49} (40 ^{±0.7})			2-110	
TH-143-2				◆ 2.94 ^{±0.49} (30 ^{±5})			2-110	
TH-143-3				◆ 1.96 ^{±0.49} (20 ^{±5})			2-110	
TH-144-1A				◆ 1.37 ^{±0.2} (14 ^{±2})			2-119	
TH-144-2A				◆ 1.08 ^{±0.15} (11 ^{±1.5})			2-119	
TH-144-3A				◆ 0.69 ^{±0.15} (7 ^{±1.5})			2-119	
TH-155				左右セット時のトルク: Rated torque (Pair) : 2.6 ^{±0.4} (26.6 ^{±4}) ◆			2-122	
TH-161		◆ 0.34 ^{±0.05} (3.5 ^{±0.5})					2-120	
TH-174		◆ 0.34 ^{±0.1} (3.5 ^{±1})					2-121	
TH-145				チルト方向: Tilt Direction : 5.88 ^{±0.98} (60 ^{±10}) ◆			二軸タイプ Two pivots-type 2-128	
				スイベル方向: Swivel Direction : 2.45 ^{±0.49} (25 ^{±5}) ◆				
TH-153				チルト方向: Tilt Direction : 5.88 ^{±0.98} (60 ^{±10}) ◆			2-129	
				スイベル方向: Swivel Direction : 2.45 ^{±0.49} (25 ^{±5}) ◆				
TH-162				◆ 0.49 ^{±0.1} (5 ^{±1})			2-126	
TH-168				固定ブラケット(A)単体のトルク : 1.37 ^{±0.2} (14 ^{±2}) ◆			その他 Others 2-127	
TH-171				◆ 0.0785 ^{±0.294} (0.8 ^{±0.3})				
TH-176				◆ 0.35 ^{±0.2} (3.6 ^{±2})				

■製品参考形状 Forms of the products for reference

